

Model Comparison

	MINI STATION	MINI BASIC	MINI PLATINUM	PRO BASIC (WASH)	PRO PLATINUM (WASH)	PRO PLATINUM (WASH/DRY)
 Operation mode	Manual, 3-in-1	Semi-automatic	–	Fully automatic -- wheel the bike in, press start, and the machine handles cleaning (and drying, on Wash/Dry).		
 Dimensions / Weight	1435 × 1030 × 1220 mm (L × W × H); 3340 mm with ramps; about 100 kg	1435 × 1030 × 1220 mm (L × W × H); 3340 mm with ramps; 215-240 kg	1100 × 1150 × 1200 mm (L × W × H); 3100 mm with ramps; 220-240 kg	2365 × 1255 × 1235 mm (L × W × H); 4200 mm with ramps; 550-650 kg (depending on configuration)		
 Power connection	–	230 V standard supply; 1.1 kVA (ECO) / 0.55 kVA (Standard)	–	400 V three-phase, or solar with 230 V; 400 V / 16 A connection required		
 Water usage	Under 1 litre per minute.	–	Approx. 3 L per wash in ECO mode (closed circuit)	Approx. 3 litres per wash on average in ECO mode (closed loop through the filter system). Very dirty bikes use fewer washes per fill; less dirty bikes more. Approx. 12 litres per wash in Standard mode (fresh water, 1/2" connection).		
 Oil separator	External oil and sludge separator: optional accessory.	External oil and sludge separator: optional accessory.	Built-in oil separator (integrated).	External oil and sludge separator: optional accessory. (Not integrated.)		
 Dryer	Built-in air dry (LuftWASH)	Touch-controlled hand dryer (optional)	Touch-controlled hand dryer (optional)	None	None (optional upgrade)	Integrated, 8 blowers

– not published for this model. Current prices: cyclewash.com