

CYCLEWASH · DATASHEET

Mini Range

Two semi-automatic wash levels – same footprint, choose your finish.



Mini Basic

BLACK

1435 × 1030 × 1220 mm (L × W × H);
3340 mm with ramps
DIMENSIONS

215–240 kg
WEIGHT

Operation mode	Semi-automatic: automatic wheel cleaning with brushes; pre-clean and dry with the Station combo.
Power connection	230 V standard supply; 1.1 kVA (ECO) / 0.55 kVA (Standard)
Modes	ECO mode and Standard fresh-water mode
Tank / pump	Approx. 90 L tank; pump circulates up to 30 L/min at max. 1 bar circuit pressure.
Dryer	Touch-controlled hand dryer (optional)
Oil separator	External oil and sludge separator: optional accessory.



Mini Platinum

FULL STAINLESS STEEL

1100 × 1150 × 1200 mm (L × W × H);
3100 mm with ramps
DIMENSIONS

220–240 kg
WEIGHT

Material	Full stainless steel
Water usage	Approx. 3 L per wash in ECO mode (closed circuit)
Tank / pump	Approx. 90 L tank; pump circulates up to 30 L/min at max. 1 bar circuit pressure.
Dryer	Touch-controlled hand dryer (optional)
Oil separator	Built-in oil separator (integrated).
Compliance	DEKRA-tested, CE-compliant, IP54 control cabinet

UPGRADE PATH

Mini Station (Manual) → Mini Basic (Semi-Automatic) → Mini Platinum (Premium, full stainless steel). Every step is compatible; start simple, scale when ready.

Maintenance contract: Annual maintenance contract (price on request). Covers routine maintenance and a phone hotline (Mon-Fri). Wear parts are consumables, billed separately. A minimum 1-year term applies to every new machine.