

CYCLEWASH · DATASHEET

Pro Range

Fully automatic -- wheel the bike in, press start, and the machine handles cleaning (and drying, on Wash/Dry).



2365 × 1255 × 1235 mm (L × W × H); 4200 mm with ramps DIMENSIONS	550-650 kg (depending on configuration) WEIGHT	400 V three-phase, or solar with 230 V; 400 V / 16 A connection required POWER CONNECTION	Approx. 3 litres per wash on average in ECO mode (closed loop through the filter system). Very dirty bikes use fewer washes per fill; less dirty bikes more. WATER USAGE (ECO)
--	--	---	--

Pro Basic	WASH	Pro Platinum	WASH	Pro Platinum	WASH/DRY
Edition Black Edition (100% recycled HDPE housing)		Edition Platinum Edition (stainless steel housing)		Edition Platinum Edition (stainless steel housing)	
Dryer None		Dryer No dryer. A hand dryer or the integrated dryer with 8 blowers (as fitted on Pro Platinum Wash/Dry) can be added.		Dryer Integrated dryer, 8 blowers.	

SPECIFICATIONS – ALL PRO VARIANTS

Dimensions 2365 × 1255 × 1235 mm (L × W × H); 4200 mm with ramps	Drain 1" drain required
Weight 550-650 kg (depending on configuration)	Housing & construction Plastic and stainless-steel housing; polyethylene/polyurethane brushes; polycarbonate side windows; lockable castors, can be moved empty on level ground.
Delivery Ready approx. 10-14 weeks after receipt of payment.	

Power connection	400 V three-phase, or solar with 230 V; 400 V / 16 A connection required	Self-service operation	PLC-controlled wash programme with adjustable wash duration. Cashless payment terminal optional. Door interlock: will not start with a door open, and stops automatically if a door is opened mid-wash.
Modes	ECO (closed water circuit) / Standard (fresh water)	Filter service	Filter system checked weekly, cleaned or replaced as needed; nozzle heads have internal filters, checked at the same time.
Water usage (ECO)	Approx. 3 litres per wash on average in ECO mode (closed loop through the filter system). Very dirty bikes use fewer washes per fill; less dirty bikes more.	Oil / sludge separator	External oil and sludge separator: optional accessory. (Not integrated.)
Water usage (Standard)	Approx. 12 litres per wash in Standard mode (fresh water, 1/2" connection).	Compliance	CE marking and Declaration of Conformity provided.
Tank / pump	Approx. 210 L recycling tank; pump circulates up to 30 L/min at max. 1 bar circuit pressure.	Maintenance contract	On request